

# 180

## PANORAMIC 180 DEGREE VISION !

Ultra-panoramic, the new 180 goggles are a concentration of innovation: style, ergonomics and high comfort thanks to their flexible bi-material ventilated frame. 180 is also compatible with respirator masks.

 PLATINUM®



180° panoramic vision



Upper ventilation




100 g



180APSI

- + WIDE ADJUSTABLE STRAP
- + ALL-ROUND VISION
- + COMPATIBLE WITH A RESPIRATOR HALF MASK

- + FITS OVER PRESCRIPTION GLASSES
- + INDIRECT VENTILATION
- +  PLATINUM® (P) COATING

**bolle**  
SAFETY

# 180

## PANORAMIC 180 DEGREE VISION !

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
180	Clear ventilated	180APSI	2C-1,2 ☞ 1 BT KN €€	☞ EN166 3 4 BT €€	Anti-scratch /Anti-fog (☞)

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

- B.** Low energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

- K.** Resistance to surface damage by fine particles (optional)
- N.** Resistance to fogging (optional)
- €€ European standard ☞ Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets.
  4. Large dust particles > 5 microns.
- B.** Low energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
  - T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
  - €€ European standard ☞ Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

PACKAGING AND EAN 13 CODE	
	180APSI
Individual plastic bag	3660740007584
Box of 5 safety goggles	3660740107581
120 safety goggle per outer pack	3660740207588

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 5
FRAME	PP/TPV
TEMPLES	Non applicable
STRAP	Polyester
FOAM	No



05/01/2017

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY