LYON BOLD & TIMELESS

Don't let anything stop you. Make your eyes feel more comfortable staring at a screen all day (or night) with our black glasses. Combining boldness and style, our timeless women's frame is compatible with all types of lenses.

SUPPLIED WITH: RX KIT (box, case, microfiber cloth, user instruction)



AVAILABLE TECHNOLOGIES

P=03LU

MODULATOR

→L\TINUM

VERSIONS



- PREMIUM ACETATE FRAME
- CAT-EYE WOMEN STYLE
- OPTIONAL BLUE LIGHT PROTECTIVE COATING AVAILABLE





LYON

REFERENCE	VERSION	SIZE	TEMPLES	WEIGHT	FRAME MARKING	STANDARDS
PXFLYON108	BLACK	53/17	140 mm	25 g	\\\ \(\) (€ \\\\\\\\\\\\\\\\\\\\\\\\\\	ISO 12870

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO C€ STANDARDS WILL BE SENT ON REQUEST.

PACKAGING & EAN13 CODE

SINGLE

Size: 17.4 x 7.7 x 5.7 mm

3660740014254

CUSTOM CODE: 90031100

ASSEMBLY RESTRICTIONS

MAXIMUM SPHERE POWER

+10/-10

MAXIMUM CYLINDER

+/-5

GENERAL SPECIFICATIONS								
CURVE	4 - SLIGHTLY CURVED	LENS MATERIAL	PC , CR39					
FRAME	ACETATE - FULL FRAME	CORRECTIONS AVAILABLE	SINGLE VISION / BIFOCAL / DEGRESSIVE / PROGRESSIVE					
STRAP		FOAM						



CLEANING & STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or

STORAGE: All products must be stored in a dry and clean environment.















MADE IN: CN

DATASHEET: 05-24-2023

bolle-safety.com

Europe Headquarters 34 rue de la Soie 69100 Villeurbanne P: 00 33 (0) 4 78 85 23 64

U.K. & Ireland Unit C83-Barwell Business Park Leatherhead Road - Chessington Surrey-KT9 2NY-UK P:00 44 (0)208 391 4700

USA Office 2810 Caribou Court, Suite 160 Carlsbad, CA 92010 United States of America P:800 222 6553

Asia-Pacific Office 32-40 Fairchild Street heatherton VIC 3202 Australia P:1300 138 098

