RUSH+

FOR HEALTHCARE PROFESSIONALS

This advanced eye protection was specifically designed for healthcare professionals; its design combines ultimate protection and comfort to help reduce workplace accidents and slow the spread of viruses. Equipped with an **anti-scratch and anti-fog coating** on both sides of the lenses, RUSH+ ensures long-lasting comfort, performance and reliability.



RUSH+ is customized for: lens marking, colored temples...

Information & conditions: salesUSA@bolle-safety.com

0.95 oz

- **UPPER PROTECTION**
- **★** → LATINUM ANTI-SCRATCH & ANTI-FOG COATING (+)
- **+** CO-INJECTED, ULTRA-FLEX TEMPLES
- **H** NON-SLIP ADJUSTABLE BRIDGE
- **WASHABLE AND REUSABLE**



RUSH-

FOR HEALTHCARE PROFESSIONALS

MODEL	ODEL VERSIONS REFERENCES LENS MARKINGS		FRAME MARKINGS			COATINGS				
			EN166	ANSI	AS/NZS	EN166	ANSI	AS/NZS		
RUSH+	Clear	PSSRUSP085	2C-1.2 😭 1 FT KN €€	₩ Z87+ U6	₩ 10	₩ EN166 FT C €	₩ Z87+	AS/NZS 1337.1 LIC25481	Anti-scratch/Anti-fog	Ţ

LENS MARKING

Manufacturer name

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

- K. Resistance to surface damage by fine particles
- N. Resistance to fogging
- C€ European standard
- O. Range of luminous transmittance 80-100% (clear)
- 2. Range of luminous transmittance 18-43% (smoke)

Z87+ = Impact rated for Plano product Tested and approved to ANSI Z81.1-2015

Lens type

 Clear = none

 Welding = W and scale number from 1.3 to 14 • UV filter = U and scale number from 2 to 6 Visible light filter = L and scale number from 1.3 to 10 IR filter = R and scale number from 1.3 to 10

= V Variable tint = S Special purpose

A WARNING: Reproductive Harm - www.P65Warnings.ca.gov

TECHNOLOGIES

*PLATINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the glasses or goggles in a microfiber pouch

STORAGE: All products must be stored in a dry and clean environment.















FRAME MARKING

Manufacturer name

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorizes use for high speed particles at extreme temperatures.
- C€ European standard

Z87+ = Impact rated for Plano product Tested and approved to ANSI Z81.1-2015

Country of origin: Taiwan

ANSI: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Maximum protection for glasses. Use for high speed particles at extreme temperatures.

AS/NZS 1337,1:2010: Tested & approuved to AS/NZS 1337,1,2010 for medium impact protection. Resists a 6mm at 45 m/s.

Bollé Safety product approval certificates to standards will be sent on

CHARACTERISTICS					
LENSES	PC - 2,2 mm - Curve 9				
FRAME	-				
TEMPLES	PC + TPR				
SPARE LENSES	No				

PACKAGING AND EAN13 CODE				
	PSSRUSP085			
Individual plastic bag	3660740013042			
10 safety glasses per inner box	3660740113049			
200 safety glasses per outer pack	3660740213046			

03/31/2021

Bollé Safety-USA 2810 Caribou Court, Suite 160 Carlsbad, CA 92010 800-222-6553 salesUSA@bolle-safety.com

