

# ILUKA

## THIN AND ULTRA-ENVELOPING

Thin, light and ultra-enveloping, ILUKA is suitable for narrow faces. Its thin co-injected temples will provide optimal support throughout the day and will easily fit under a protective helmet.



ILUPSI



ILUPSF















22g

- + LIGHTWEIGHT AND ULTRA-ENVELOPING**
- + CO-INJECTED BI-MATERIAL PC/TPR TEMPLES**
- + THIN, ERGONOMIC AND COMFORTABLE TEMPLES ADAPTABLE WITH OTHER PPE**
- + SUITABLE FOR NARROW FACES**

**bollé**  
SAFETY

# ILUKA

## THIN AND ULTRA-ENVELOPING

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
ILUKA	 Clear	ILUPSI 	2C-1,2  1 FT 	 EN166 FT 	Anti-scratch/Anti-fog
	 Smoke	ILUPSF 	5-3,1  1 FT 	 EN166 FT 	Anti-scratch/Anti-fog

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:


F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging


CE European standard  Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

CE European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

### PACKAGING AND EAN13 CODE

	ILUPSI	ILUPSF
Individual plastic bag	3660740008857	3660740008864
10 safety spectacles per inner box	3660740108854	3660740108861
240 safety spectacles per outer pack	3660740208851	3660740208868

### CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	-
TEMPLES	PC + TPR



Non-contractual pictures

10/01/2019

Europe Bollé Safety  
34 rue de la Soie  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

[bolle-safety.com](http://bolle-safety.com)

**bolle**  
SAFETY