

COMBAT

MODULARITY & PERFORMANCE

These highly performant and versatile hybrid spectacles are specifically designed for tactical environments, surpassing both U.S. and global military impact requirements. Featuring an easily replaceable fog and scratch-resistant ballistic mono-lens in multiple tints, COMBAT offer superior visual definition. The dual temple/strap system ensures an optimal fit and retention, making them ideal for operators to tackle any mission.

SUPPLIED WITH : Strap - Case - Microfiber pouch

 50 G

- + **HIGH-IMPACT BALLISTIC PROTECTION: MIL & STANAG**
- + **PLATINUM COATING : ANTI-SCRATCH & ANTI-FOG**
- + **ERGONOMIC TEMPLES COMPATIBLE WITH COMMUNICATIONS SYSTEMS AND BALLISTICS HELMETS**
- + **NON-SLIP NOSE BRIDGE**



TECHNOLOGIES

CSP

PLATINUM

VERSIONS



COMBKITN



COMBKITNRX



KITFSCOMB



TACTICALRXKIT



FACOMBPSI



FACOMBPSF

NON-CONTRACTUAL PICTURES

COMBAT						
REFERENCE	VERSION	LENS MARKING	FRAME MARKING	BALLISTIC RESISTANCE V50 STANAG 4296	MIL-PRF	COATING
 COMBKITN	 COPPER FLASH - SMOKE	CLEAR : 2C-1.2  1 BT KN CE SMOKE : 5-3.1  1 BT KN CE COPPER : 5-1.4  1 BT KN CE	 EN166 FT CE	CLEAR : 824.2 KM/H - 229 M/S SMOKE : 849.6 KM/H - 236 M/S COPPER : 918 KM/H - 255 M/S	32432A	PLATINUM
 COMBKITNRX	 COPPER FLASH - SMOKE	CLEAR : 2C-1.2  1 BT KN CE SMOKE : 5-3.1  1 BT KN CE COPPER : 5-1.4  1 BT KN CE	 EN166 FT CE	CLEAR : 824.2 KM/H - 229 M/S SMOKE : 849.6 KM/H - 236 M/S COPPER : 918 KM/H - 255 M/S	32432A	PLATINUM
 FACOMBPSI	 CLEAR	2C-1.2  1 BT KN CE		824.2 KM/H - 229 M/S	32432A	PLATINUM
 FACOMBPSF	 SMOKE	5-3.1  1 BT KN CE		849.6 KM/H - 236 M/S	32432A	PLATINUM

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO CE STANDARDS WILL BE SENT ON REQUEST.

BALLISTIC STANDARDS

STANAG
4296

MIL-PRF
32432A

OPTIONAL ACCESSORIES				
REFERENCE	DESCRIPTION	SINGLE:	INNER BOX:	OUTER PACK:
KITFSCOMB	FOAM AND STRAP (KIT)	3660740000189	3 660 740 100 186	3 660 740 200 183
TACTICALRXKIT	RX INSERT	3660740008031	3 660 740 108 038	3 660 740 208 035

GENERAL SPECIFICATIONS			
LENS	POLYCARBONATE - 2.7 MM - CURVE 9	CE	EN166 - EN170
FRAME	NYLON/PC/TPR - RIMLESS	ANSI	ANSI Z87.1-2010
STRAP	NYLON POLYESTER	AS/NZS	

KNOW MORE ABOUT MARKINGS:

CLICK

OR SCAN:



CLEANING & STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.