

SENTINEL

ballistic sunglasses

Certified to STANAG 2920 and EN172, these SENTINEL ballistic protection sunglasses ensure maximum protection against any event. Thanks to its adjustable non-slip bridge, its flexible temples and its ultra enveloping design, SENTINEL will provide you comfort and protection. SENTINEL is available in **smoke and CSP**  **PLATINUM**, **red flash and ESP**.

ULTRA FLEXIBLE AND COMFORTABLE FRAME

BALLISTIC POLYCARBONATE LENS

(NEW)

 PLATINUM COATING

ON SMOKE AND CSP VERSIONS




NON SLIP STRAIGHT
TEMPLES

ADJUSTABLE NON SLIP BRIDGE



PLATINUM (P)

The new exclusive PLATINUM coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.



VERSIONS AVAILABLES :



SENTIPSF



SENTIESP



SENTIFLASH




SENTICSP

SUPPLIED WITH :



Supplied with microfibre pouch and individual soft carry case



SENTINEL

ballistic sunglasses

markings / norms

Model	Reference	Version	Lens markings	Frame marking	V50 Ballistic Resistance STANAG 2920	ANSI/MIL	Coatings
SENTINEL	SENTIPSF	 Smoke	5-3,1 ☞ 1 FT KN CE	☞ EN166 FT CE	657,7 km/h - 182,7 m/s	ANSIZ87.1-2010	◆ PLATINUM (P)
	SENTIFLASH	 Red flash	5-3,1 ☞ 1 FT CE	☞ EN166 FT CE	668,5 km/h - 185,7 m/s	ANSIZ87.1-2010	ASAF
	SENTIESP	 ESP	5-1,4 ☞ 1 FT CE	☞ EN166 FT CE	640,8 km/h - 178 m/s	ANSIZ87.1-2010	ASAF
	SENTICSP	 CSP	5-1,4 ☞ 1 FT KN CE	☞ EN166 FT CE	704,5 km/h - 195.7m/s	ANSIZ87.1-2010	◆ PLATINUM (P)

CHARACTERISTICS

LENS:

Ballistic PC lens - 2.2 mm - Base 8
PLATINUM coating (on smoke and CSP versions)

CHARACTERISTICS

TEMPLES:

Comfort bi-material (PC + TPR)
non-slip temples

FRAME: Available in mat black

WEIGHT: 25 g

**HIGH
RESISTANCE**

packaging and ean13 code :

Model	Reference	Unit	Inner box	Units	Outer box	Units
SENTINEL	SENTIPSF	3660740001230	X	X	3660740201234	x 95
	SENTIFLASH	3660740001247	X	X	3660740201241	x 95
	SENTIESP	3660740001254	X	X	3660740201258	x95
	SENTICSP	3660740007942	X	X	3660740207946	x 95

Notified laboratories for certification:



06/01/2017