

PILOT NEO

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

Its co-injected, vented frame guarantees unequalled adaptability and comfort while its neoprene strap improves its resistance to temperature, fire, tearing and chemical products. The PILOT NEO is perfectly adapted to oil and gas environments.

 PLATINUM



PSGPIL2-L17



PSGPIL2-L16








3 oz

- + EXCELLENT FIELD OF VISION**
- + PP/TPR TWIN-MATERIAL FRAME**
- +  PLATINUM COATING (P)**
- + ADJUSTABLE NEOPRENE STRAP**
- + FITS OVER PRESCRIPTION GLASSES**

bolle
SAFETY

PILOT NEO

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
PILOT NEO	 Clear Vented	PSGPIL2-L16	 Z87+ U6	 Z87+ D3/D4	Anti-scratch/anti-fog (☑)
	 CSP Vented	PSGPIL2-L17	 Z87+ U6S	 Z87+ D3/D4	Anti-scratch/anti-fog (☑)

LENS MARKING

- **Crown** = Manufacturer Mark
- **Z87+** = Impact rated for Plano product - tested and approved to ANSI Z81.1-2015
- **Lens type**
 - Clear = none
 - Welding = W and Shade number from 1,3 to 14
 - UV filter = U and scale number from 2 to 6
 - Visible light filter = L and scale number from 1,3 to 10
 - IR filter = R and scale number from 1n3 to 10
 - Variable tint = V
 - Special purpose = S

⚠ **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov

FRAME MARKING

- **Crown** = Manufacturer Mark
- **Z87+** = Impact rated for Plano product - tested and approved to ANSI Z81.1-2015
 - Splash/droplet protection = D3
 - Nuisance Dust protection = D4
 - Fine Dust protection = D5
- **Country of origin** = Taiwan

ANSI: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Maximum protection for glasses. Use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to ANSI standards will be sent on request.

TECHNOLOGIES

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.



The exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the glasses or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE		
	PSGPIL2-L16	PSGPIL2-L17
Individual plastic bag	3660740009755	3660740009762
5 safety goggles per inner box	3660740109752	3660740109769
80 safety goggles per outer pack	3660740209759	3660740209766

CHARACTERISTICS	
LENSES	PC - 2,1 mm - Curve 5,5
FRAME	PP + TPR
TEMPLES	Non applicable
STRAP	Neoprene
FOAM	No
SPARE LENSES	No



01/2021

Bollé Safety USA
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
salesUSA@bolle-safety.com

bollesafety-usa.com

bolle
SAFETY