


ASSAULT

ballistic sunglasses

Certified to STANAG 2920, EN166, EN170 and EN172, these ASSAULT ballistic protection sunglasses ensure maximum protection in all circumstances. Thanks to its adjustable bridge and its flexible, straight non-slip temples, ASSAULT provides comfort and protection.

ASSAULT is available in **smoke, CSP and TWILIGHT**  **PLATINUM** coating versions.

HIGHLY FLEXIBLE,
COMFORTABLE FRAME

 **PLATINUM** COATING
ON SMOKE, CSP AND TWILIGHT VERSION

BALLISTIC POLYCARBONATE
LENS




NON-SLIP BRIDGE

STRAIGHT NON-SLIP
TEMPLES

PLATINUM

The new exclusive PLATINUM coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.



VERSIONS AVAILABLES :



ASSAPSF



ASSATWI




ASSACSP

SUPPLIED WITH :















Supplied with microfibre pouch and individual soft carry case



ASSAULT

ballistic sunglasses

markings / norms

Model	Reference	Version	Lens markings	Frame marking	V50 Ballistic Resistance STANAG 2920	ANSI/MIL	Coatings
ASSAULT	ASSAPSF	 Smoke	5-3,1  1 FT KN C€	 EN166 FT C€	670,3 km/h - 186,2 m/s	ANSIZ87.1-2010 MIL-PFR-31013	 PLATINUM
	ASSATWI	 TWILIGHT	5-2  1 FT KN C€	 EN166 FT C€	674,3 km/h - 187,3 m/s	ANSIZ87.1-2010 MIL-PFR-31013	 PLATINUM
	ASSACSP	 CSP	5-1,4  1 FT KN C€	 EN166 FT C€	748,4 km/h - 207,9m/s	ANSIZ87.1-2015	 PLATINUM

CHARACTERISTICS

LENS:
Ballistic PC lens - 2.2 mm - Base 8
PLATINUM coating (on smoke, CSP
and TWILIGHT version)
Integrated lateral protection

CHARACTERISTICS

TEMPLES:
Comfort non slip bi-material temples
(Nylon + PVC)
FRAME: Available in mat black
WEIGHT: 28 g

**HIGH
RESISTANCE**

packaging and ean13 code :

Model	Reference	Unit	Inner box	Units	Outer box	Units
ASSAULT	ASSAPSF	3660740000783	3660740100780	X	3660740200787	x 95
	ASSATWI	3660740000806	3660740100803	X	3660740200800	x 95
	ASSACSP	3660740000806	3660740108083	X	3660740208080	x 95

Notified laboratories for certification:



24/04/2019