

+ MICROFIBER POUCH INCLUDED

RUSH+ provides a panoramic field of vision and offers a hard core design thanks to its flexible co-injected temples. Also ultra-light, RUSH+ ensures perfect optical quality and ultimate comfort.

Permanent coating on both sides of the lens gives them a high resistance to scratching, and delays the onset of fogging. Certified K & N (EN166) PLATINUM[®] resists to the most aggressive chemicals.

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

TWILIGHT

The TWILIGHT technology offers the advantages of ESP and more. Designed and used in low light conditions, it improves contrast. Its light transmission rate is perfect for outdoors, particularly early morning and late evening. TWILIGHT fiters 76% of blue light.

VERSIONS

DESCRIPTION

RUSH+

bollé SAFETY STANDARD ISSUE

MODEL	FRAME	VERSIONS	REFERENCES	LENS MARKINGS	FRAME MARKINGS	V50 BALISTIC RESISTANCE STANAG 2920	ANSI/MIL	COATING
RUSH+	Black	Clear	PSSRUSP064	🗁 Z87+ U6	\ Z87+	-	-	ASAF 쿠
	Black	Smoke	PSSRUSP443	🗁 Z87+ U6S	☆ Z87+	-	-	ASAF 쿠
	Black	CSP	PSSRUSPC13	🗁 Z87+ U6S	\ [_] Z87+	-	-	ASAF 쿠
	Black	Twilight	PSSRUSPT09	🗁 Z87+ U6S	\ [_] Z87+	-	-	ASAF 🄁
	Foam & Strap Kit	-	RUSHKITFS	-	-	-	-	-

Lens markings

287+. Impact rated for Plano product - tested and approved to ANSI Z87.1-2010 ☆ Manufacturer name

Lens Type:

 $\begin{array}{l} \mbox{Clear} = \mbox{none} \\ \mbox{Welding} = W \mbox{ and Shade number from 1,3 to 14} \\ \mbox{UV filter} = U \mbox{ and scale number from 2 to 6} \\ \mbox{Visible light filter} = L \mbox{ and scale number from 1,3 to 10} \\ \mbox{IR filter} = R \mbox{ and scale number from 1,3 to 10} \\ \mbox{Variable tint} = V \\ \mbox{Special purpose} = S \end{array}$

Frame markings

Manufacturer name Country of Origin: Taiwan **Z87+.** Impact rated for Plano product - tested and approved to ANSI Z87.1-2010 **Mechanical strength symbols:**

ANSI. guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc. Maximum protection for glasses. Use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to ANSI standards will be sent on request.

	PSSRUSP064	PSSRUSP443	PSSRUSPC13	PSSRUSPT09	RUSHKITFS
EAN13 Unit pack	3660740010751	3660740010768	3660740010775	3660740010782	3660740006488
EAN13 Inner pack	3660740110758	3660740110765	3660740110772	3660740110789	3660740106485
(number of unit per inner pack)	(10 units)	(10 units)	(10 units)	(10 units)	(20 units)
Size // Weight	24x18x9 cm	24x18x9 cm	24x18x9 cm	24x18x9 cm	28x16x7 cm
Inner pack	0.6 kg	0.6 kg	0.6 kg	0.6 kg	0.3 kg
EAN13 Carton	3660740210755	3660740210762	3660740210779	3660740210786	3660740206482
(number of unit per master pack)	(200 units)	(200 units)	(200 units)	(200 units)	(240 units)
Size // Weight	60x50x37 cm	60x50x37 cm	60x50x37 cm	60x50x37 cm	46x37x28 cm
Master pack	12.8 kg	12.8 kg	12.8 kg	12.8 kg	4.7 kg

Maintenance: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case. Storage: All products must be stored in a dry and clean environment.

RUSH+					
Lens	PC - 2.3 mm - Curve 9				
Temples	PC + TPR				
Strap	Nylon - 15mm				
Foam	SBR + Nylon				
Spare lens	No				
Country of Origin	Taiwan				



For more information on this product and the BSSI range, visit:

bollesafety-usa.com

BOLLÉ SAFETY 1896 Rutherford Rd Carlsbad, CA 92008 USA

PACKAGING

MARKINGS

LABORATORIES