

# SUPERBLAST

## GREATER COMFORT AND PROTECTION

SUPERBLAST goggles feature a softer frame, the PLATINUM+P Anti-Fog/Anti-Scratch coating and a simplified assembly system for the goggle visor.



4 oz.



40295 +P



40296 +P



40298

VISOR ONLY



**+ PLATINUM +P ANTI-FOG & ANTI-SCRATCH COATING**

**+ ALL-ROUND VISION**

**+ BALL-PIVOT**

**+ ADJUSTABLE STRAP**

**+ OVERFLOW CHUTE FOR LIQUIDS**

**+ FITS OVER PRESCRIPTION GLASSES**

**+ COMPATIBLE WITH HALF-MASK RESPIRATOR**

**bolle**  
SAFETY

# SUPERBLAST

## GREATER COMFORT AND PROTECTION



MODEL	SKU	LENS OPTIONS	FRAME COLOR	UPC	LENS MARKING	TEMPLE/ FRAME MARKING	COATINGS	INNER PACK	MASTER PACK
SUPERBLAST Ventilated	40295	Clear	Blue	0-54917-33783-4	☙ Z87+U6	☙ Z87+D3/D4	ASAF/P	5	120
SUPERBLAST Sealed	40296	Clear	Blue	0-54917-33784-1	☙ Z87+U6	☙ Z87+D3/D4/D5	ASAF/P	5	120
SUPERBLAST Visor	40298	Blue	Blue	0-54917-33786-5	NA	NA	NA	NA	180

Bollé Safety Letters of Conformity are available upon request.

### LENS MARKING

Certified ISEA ANSI Z87.1-2015

### FRAME MARKING

The SUPERBLAST'S are rated D3/D4 and D3/D4/D5 for protection from liquid splash and dust and from liquid splash, dust and fine dust.

### PROP 65

**WARNING:** Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNOLOGY

#### PLATINUM<sup>®</sup>

The new exclusive scratch and fog resistant PLATINUM<sup>®</sup> coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.