## TOKYO CLASSIC & MINIMALIST

Classic and minimalist, the TOKYO frame will protect your sight. Its shiny black and gunmetal design is compatible with all types of lenses.

SUPPLIED WITH: RX KIT (box, case, microfiber cloth, user instruction)

- 4 LIGHTWEIGHT METAL FRAME
- HEN STYLE
- OPTIONAL BLUE LIGHT PROTECTIVE COATING AVAILABLE



P⇒o⊃Lu MODULATOR →PL\TINUM





PXFTOKY100







TOKYO

REFERENCE	VERSION	SIZE	TEMPLES	WEIGHT	FRAME MARKING	STANDARDS
PXFTOKY100	BLACK-GUNMETAL	54/18	140 mm	24 g	\\\ \( \) ( € \\\\\\\\\\\\\\\\\\\\\\\\\\	ISO 12870

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO C€ STANDARDS WILL BE SENT ON REQUEST.

PACKAGING & EAN13 CODE

SINGLE

Size: 17.4 x 7.7 x 5.7 mm

3660740014285

**CUSTOM CODE:** 90031100

## ASSEMBLY RESTRICTIONS

MAXIMUM SPHERE +10/-10 POWER	M A X I M U M C Y L I N D E R	+/-5
------------------------------------	----------------------------------	------

GENERAL SPECIFICATIONS							
CURVE	4 - SLIGHTLY CURVED	LENS MATERIAL	PC , CR39				
FRAME	METAL - FULL FRAME	CORRECTIONS AVAILABLE	SINGLE VISION / BIFOCAL / DEGRESSIVE / PROGRESSIVE				
STRAP		FOAM					



CLEANING & STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or

STORAGE: All products must be stored in a dry and clean environment.















MADE IN: CN

**DATASHEET:** 05-24-2023

bolle-safety.com

**Europe Headquarters** 34 rue de la Soie 69100 Villeurbanne P: 00 33 (0) 4 78 85 23 64

U.K. & Ireland Unit C83-Barwell Business Park Leatherhead Road - Chessington Surrey-KT9 2NY-UK P:00 44 (0)208 391 4700

**USA Office** 2810 Caribou Court, Suite 160 Carlsbad, CA 92010 United States of America P:800 222 6553

Asia-Pacific Office 32-40 Fairchild Street heatherton VIC 3202 Australia P:1300 138 098

