# CONTOUR





#PSSCONTC13

**★** MICROFIBER POUCH INCLUDED

#PSSCONTO64

0.74 oz of strength: sturdy, protective, comfortable and lightweight. CONTOUR is the most extreme everyday sun and safety protection eyewear

#PSSCONT443

PLATINUM® (†P) ASAF Coating
Permanent coating on both sides of the lens gives them a high
resistance to scratching, and delays the onset of fogging. Certified
K & N (EN166) PLATINUM® resists to the most aggressive chemicals.

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

POLARIZED
A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.



**POLARIZED** 

#PSSCONTP11

# CONTOUR



MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	V50 BALISTIC RESISTANCE STANAG 2920	ANSI/MIL	COATINGS
CONTOUR	Clear	PSSCONT064	₩ Z87+ U6	₩ Z87+	-	-	Anti-scratch/anti-fog
	Smoke	PSSCONT443	₩ Z87+ U6S	₩ Z87+	-	-	Anti-scratch/anti-fog 🔁
	CSP	PSSCONTC13	₩ Z87+ U6S	₩ Z87+	-	-	Anti-scratch/anti-fog 🔁
	POLARIZED	PSSCONTP11	₩ Z87+ U6S	₩ Z87+	-	-	Anti-scratch

# Lens markings

**Z87+.** Impact rated for Plano product - tested and approved to ANSI Z87.1-2010 ✓ Manufacturer name

## Lens Type:

Clear = none

Welding = W and Shade number from 1,3 to 14

UV filter = U and scale number from 2 to 6

Visible light filter = L and scale number from 1,3 to 10

IR filter = R and scale number from 1,3 to 10

Variable tint = V

Special purpose = S

Bollé Safety product approval certificates to ANSI standards will be sent on request.

# Frame markings

Manufacturer name

Country of Origin: Taiwan

**Z87+.** Impact rated for Plano product - tested and approved to ANSI Z87.1-2010

# Mechanical strength symbols:

ANSI. guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc. Maximum protection for glasses. Use for high speed particles at extreme temperatures.

	PSSCONT064	PSSCONT443	PSSCONTC13	PSSCONTP11
EAN13 Unit pack	3660740010942	3660740010959	3660740010966	3660740011635
EAN13 Inner pack	3660740110949	3660740110956	3660740110963	3660740111632
(number of unit per inner pack)	(10 units)	(10 units)	(10 units)	(10 units)
Size // Weight	24x18x9 cm	24x18x9 cm	24x18x9 cm	24x18x9 cm
Inner pack	0.51 kg	0.51 kg	0.51 kg	0.51 kg
EAN13 Carton	3660740210946	3660740210953	3660740210960	3660740211639
(number of unit per master pack)	(240 units)	(240units)	(240units)	(240 units)
Size // Weight	60x50x37 cm	60x50x37 cm	60x50x37 cm	60x50x37 cm
Master pack	13.4 kg	13.4 kg	13.4 kg	13.4 kg

Maintenance: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case. Storage: All products must be stored in a dry and clean environment.

CONTOUR					
LENSES	PC - 2.2 mm - Curve 8				
FRAME	PC				
TEMPLES	Nylon + TPE				
STRAP	Not applicable				
FOAM	Not applicable				
Country of origin	Taiwan				















For more information on this product and the BSSI range, visit:

bollesafety-usa.com

**BOLLÉ SAFETY** 1896 Rutherford Rd Carlsbad, CA 92008 **USA**