

BL30

The BL30 offers an excellent quality/price ratio. It has an ultra **wrap-around fit** that perfectly meets all types of needs for your company. Equipped with an **anti-scratch and anti-fog coating** on both sides of the lenses, BL30 ensures absolute long-lasting comfort.

PLATINUM LITE



23 g



PSSBL30074



PSSBL30451

bLINE



ECO-PACKAGING:

Guaranteed plastic-free, this **GO GREEN** packaging is respectful of the environment. The products are wrapped in tissue paper and then stored in recycled and recyclable cardboard boxes. The user instructions are printed with vegetable ink directly onto the packaging to reduce waste.

- + UPPER PROTECTION
- + ANTI-FOG & ANTI-SCRATCH COATING ON BOTH SIDES OF THE LENSES
- + SUSTAINABLE PACKAGING
- + STOP-IN SYSTEM (ON THE HINGE OF THE TEMPLES)
- + UNIVERSAL FIT
- + WITHOUT ANY SCREWS

bolle
SAFETY

BL30

MODEL	VERSIONS	REFERENCES	LENS MARKINGS			FRAME MARKINGS			COATINGS
			EN166	ANSI	AS.NZS	EN166	ANSI	AS.NZS	
BL30	 Clear	PSSBL30074	2C-1.2  1FT €€	 Z87+U6	 IO	 EN166 FT €€	 Z87+	AS/NZS 1337.1:2010	ASAF 
	 Smoke	PSSBL30451	5-2,5  1FT €€	 Z87+U6 L2.5	 I2	 EN166 FT €€	 Z87+	AS/NZS 1337.1:2010	ASAF 

LENS MARKINGS

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- I.** The letter «I» signifies «Medium Impact» approval.
- O.** The letter «O» signifies that the product has been approved for the use both outdoors and indoors.

Others symbols:

€€ European standard  Manufacturer name

- O.** Range of luminous transmittance 80-100% (clear)
2. Range of luminous transmittance 18-43% (smoke)

FRAME MARKINGS

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Z87+ : Impact rated for Plano product - tested and approved to ANSI Z87.1-2015

AS/NZS 1337.1:2010 : Tested & approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

€€ European standard  Manufacturer name

Bollé Safety product approval certificates to standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE		
	PSSBL30074	PSSBL30451
20 safety glasses per inner box	3660740111922	3660740111939
240 safety glasses per outer pack	3660740211929	3660740211936

CHARACTERISTICS	
LENSES	PC - 2 mm - Curve 9,5
FRAME	PC
TEMPLES	PC
SPARE LENS	No



Eco packaging: Guaranteed plastic-free, this packaging is respectful of the environment. The products are wrapped in tissue paper and then stored in recycled cardboard boxes.
Inner box: 56x18x9cm // Outer pack: 76x58x30cm - Not available in single sale format.



Non-contractual pictures

01/07/2021

Europe Bollé Safety
34 rue de la Soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : uk@bollebrands.com

bolle
SAFETY