

BLAST

AN OUTSTANDING FIELD OF VISION

Unbeatable comfort and essential modular design. With the Mouth Guard, the BLAST model can be used as a face shield with equivalent protection guaranteed.



Optional Mouth Guard

ACCESSORIES

- 1669205 • Clear Lens Only
 - 1669206 • Smoke Lens Only
 - 1650015 • RX Adaptor
 - 1669204 • Mouth Guard
 - 1650014 • Lens Tear Off
- (1 Pack = 10 Sets / 4 per set)



1669101 • Blue Frame with SBR Foam / Clear Lens / Top Vent Closed



1669201 • Blue Frame with SBR Foam / Clear Lens / Indirect Top / Bottom Vents



1669203 • Blue Frame with SBR Foam / Clear Lens / Mouth Guard / Indirect Top / Bottom Vents



113g




- + EXCEPTIONAL DUST PROTECTION**
- + CAN BE WORN OVER SPECTACLES & DISPOSABLE RESPIRATORS**
- + LOW PROFILE, LIGHT WEIGHT PVC FRAME**
- + OPTIONAL MOUTH GUARD**

- + MEDIUM IMPACT & CHEMICAL SPLASH APPROVED**

bolle
SAFETY

BLAST

AN OUTSTANDING FIELD OF VISION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
BLAST	 Blue Frame with SBR Foam / Clear Lens / Top Vent Closed	1669101	CIO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Blue Frame with SBR Foam / Clear Lens / Indirect Top / Bottom Vents	1669201	CIO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Blue Frame with SBR Foam / Clear Lens / Mouth Guard / Indirect Top / Bottom Vents	1669203	CIO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

LENS MARKING

- C.** The letter 'C' signifies that the product has been tested and approved for use against splashes and is appropriate for chemical handling.
- I.** The letter 'I' signifies 'Medium Impact' approval.
- O.** The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

OCULAR LENS CATEGORY:

- O.** Range of luminous transmittance 80-100% (clear).

APPLICATIONS

- Chemical splash protection
- Cutting
- Spraying
- Dust protection
- Acid and alkaline handling
- Wood and metal work

MAIN MARKETS

- Petro Chemical
- Construction
- Manufacturing
- Paint
- Automotive
- Labs

LENSES

- 2mm polycarbonate
- 9 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear
- 99.99% UV 385 – Clear

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm
FRAME	PVC
STRAP	Yes
FOAM	SBR
SPARE LENSES	Yes

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact and chemical splash protection. Resists a 6mm at 45 m/s.

05/07/2019

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:

T.: 0800 2655 369
E: bolle@bolle.co.nz

bolle
SAFETY