

RAIDER

LENS
 + 'PLATINUM' ASAF COATING
 + BALLISTIC POLYCARBONATE MONO LENS



FRAME
 + LATERAL PROTECTION
 + HYBRID MODEL : TEMPLES OR STRAP

BRIDGE
 + NON-SLIP BRIDGE



RAIDER KIT
 #RAIDERKIT


 38 g

+ THE RAIDER KIT COMES WITH SPARE LENSES, A MICROFIBRE POUCH, A STRAP, TEMPLES AND A RIGID CARRY CASE.

VERSIONS

DESCRIPTION





















With its easy-to-change, 'PLATINUM' scratch resistant, anti-fog mono-lens in clear, yellow and smoke versions, the RAIDER ballistic glasses adapt to all your needs for maximum protection. Thanks to its dual temples/strap system and the possibility to add foam, you can now choose the version best suited to your needs.

TECHNOLOGIES

'PLATINUM' (P) ASAF Coating
 Permanent coating on both sides of the lens gives them a high resistance to scratching, and delays the onset of fogging. Certified K & N (EN166) PLATINUM® is resistant to the most aggressive chemicals.



RAIDER

MODEL	REFERENCE	VERSION	LENS MARKINGS	FRAME MARKINGS	V50 BALLISTIC RESISTANCE STANAG 4296	ANSI/MIL	COATING
RAIDER Hybrid glasses	RAIDERKIT	 Clear	2C-1.2  1 FT KN 	 EN166 FT 	695 km/h - 193 m/s	-	ASAF 
		 Yellow	2C-1.2  1 FT KN 	 EN166 FT 	713 km/h - 198 m/s	-	AS/AF 
		 Smoke	5-3.1  1 FT KN 	 EN166 FT 	666 km/h - 185 m/s	-	ASAF 
		Worn with strap	-	 EN166 BT 	-	-	-

Lens markings

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

CE European standard  Manufacturer name

Frame markings

Standards :

EN166. guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

CE European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

	RAIDERKIT
EAN13 Unit pack	3660740000776
EAN13 Inner pack (number of unit per inner pack)	-
Size // Weight Inner pack	-
EAN13 Master (number of unit per master pack)	3660740200770 (90 units)
Size // Weight Master pack	50x60x37 cm 24.2 kg

Maintenance: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

Storage: All products must be stored in a dry and clean environment.

RAIDER	
Lens	PC - 2.45 mm - Curve 8
Temples	PC
Strap	25 mm adjustable
Spare lens	-
Country of origin	Taiwan

For more information on this product and the BSSI range, visit:

bolle-safety.com

BOLLÉ SAFETY / APAC
32-40 Fairchild Street
Heatherton VIC 3202
AUSTRALIA