

NESS+

SPORTY LOOK

With Ness+ you enjoy all the benefits of the Ness model with added comfort thanks to co-injected temples. Exclusive Platinum® scratch and fog resistant coating helps you work more efficiently. Available with foam and adjustable strap, Ness+ provides protection for different risk levels.

★ PLATINUM



28g



50g



NESSPPSI



NESSPPSF



NESSPCSP



PSPNESF028



PSPNESKB04 (option)
Foam + strap



PSPUNISS01 (option)
Strap

- ✚ **ULTRA-WRAPAROUND FRAME**
- ✚ **★ PLATINUM SCRATCH AND FOG RESISTANT COATING**
- ✚ **PC/TPR CO-INJECTED TEMPLES FOR GREATER COMFORT**
- ✚ **PANORAMIC FIELD OF VISION**
- ✚ **NON-SLIP NOSE BRIDGE**

bolle
SAFETY

NESS+

SPORTY LOOK

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
NESS+	Clear	NESSPPSI	2C-1,2 1 FT KN CE	EN166 FT CE	Anti-scratch/Anti-fog
	CSP	NESSPCSP	5-1,4 1 FT KN CE	EN166 FT CE	Anti-scratch/Anti-fog
	Smoke	NESSPPSF	5-3,1 1 FT KN CE	EN166 FT CE	Anti-scratch/Anti-fog
	Clear with foam and strap	PSSNESF028	2C-1,2 1 FT KN CE	EN166 3 4 FT CE	Anti-scratch/Anti-fog
	Foam and strap (option)	PSPNESKB04	-	-	-
	Strap only (option)	PSPUNISS01	-	-	-

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

CE European standard Manufacturer name

TECHNOLOGIES

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

PLATINUM

The exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.

4. Large dust particles > 5 microns.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

CE European standard Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

	NESSPPSI	NESSPPSF	NESSPCSP	PSSNESF028	PSPNESKB04	PSPUNISS01
Individual plastic bag	3660740008543	3660740008550	3660740008567	3660740011994	3660740012007	3660740011970
Inner box	3660740108540 (10)	3660740108557 (10)	3660740108564 (10)	3660740111991 (10)	3660740112004 (20)	3660740111977 (40)
Outer pack	3660740208547 (200)	3660740208554 (200)	3660740208561 (200)	3660740211998 (200)	3660740212001 (480)	3660740211974 (480)

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 10
FRAME	-
TEMPLES	PC + TPR
BRIDGE	PVC
STRAP	Nylon/15mm/Adjustable
SPARE LENSES	No
FOAM	TPEE/SBR



Non-contractual pictures

01/05/2021

Europe Bollé Safety
34 rue de la Soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : uk@bollebrands.com

bolle
SAFETY