

BL20

ULTRA PROTECTION & EFFICIENCY

BL20 provides full head and face protection and a wide field of vision

260 G

- + ADJUSTABLE HEADBAND AND PROTECTIVE HEADGEAR
- + TILTING SHIELD
- + OPTION: ADAPTER COMPATIBLE WITH THE SPHERE MODEL SHIELD



TECHNOLOGIES

VERSIONS



BL20PI



BL20FAPI



BL20HA

BL20

USE	VERSION	REFERENCE	LENS MARKING	FRAME MARKING	COATING	STANDARD
👤	🕒 CLEAR	BL20PI	👑 1 BT CE	👑 EN166 3 BT CE	ANTI-SCRATCH	EN166
👤	🕒 CLEAR	BL20FAPI	👑 1 BT CE			EN166
👤	HELMET ADAPATOR	BL20HA		👑 EN1731 CE		EN166 - EN1731

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO CE STANDARDS WILL BE SENT ON REQUEST.

PACKAGING & EAN13 CODE

SINGLE: Size: 25.5 x 30.5 x 13 mm	INNER BOX: Size: 20.3x39.3x2.5 cm Weight: 2.5 kg	OUTER PACK: Size: 60 x 51.5 x 38.5 cm Weight: 7.8 kg
3660740003173	3660740103170 -1 pcs	366 074 020 377 -25 pcs
3660740003180	3660740103187 -10 pcs	3660740203184 -200 pcs
3660740003197	3660740103194 -1 pcs	3660740203191 -50 pcs
CUSTOM CODE: 3926909790		

GENERAL SPECIFICATIONS

LENS	POLYCARBONATE - 2.2 MM	FOAM	
CURVE		STRAP	
FRAME	HDPE -	OPTIONAL	



CLEANING & STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



MADE IN: TW

DATASHEET: 06-08-2023

bolle-safety.com

Europe Headquarters
34 rue de la Soie
69100 Villeurbanne
France
P : 00 33 (0) 4 78 85 23 64

U.K. & Ireland
Unit C83 - Barwell Business Park
Leatherhead Road - Chessington
Surrey - KT9 2NY - UK
P : 00 44 (0)208 391 4700

USA Office
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
United States of America
P : 800 222 6553

Asia-Pacific Office
32-40 Fairchild Street
Heatherton VIC 3202
Australia
P : 1300 138 098



THE PPE EYEWEAR SPECIALISTS