

# MERCURO

## 100% OUTDOOR

Stylish safety glasses with a wrap-around design, PVC nose bridge and bi-material temples for added comfort. Mercurio's bold styling coupled with Platinum® anti-scratch/anti-fog coating provides maximum protection and performance that exceeds expectations. Includes CSP for indoor/outdoor use.



 PLATINUM®



### SUPPLIED WITH

Microfiber pouch  
40107  
(for MERPOL only)



1.13 oz



MERCSP



MERPSF




MERPOL



MERPSF + UNIVSTRAP














UNIVSTRAP (option)  
Retainer strap

- + ULTRA-WRAPAROUND FRAME // LARGE FIELD OF VISION
- + NO METAL PART
- + PC/TPR CO-INJECTED TEMPLES FOR GREATER COMFORT
- +  PLATINUM® (+P) SCRATCH AND FOG RESISTANT COATING – EXCEPT FOR POLARIZED VERSION
- + NON-SLIP NOSE BRIDGE
- + SPORTY DESIGN

**bolle**  
SAFETY

# MERCURO

## 100% OUTDOOR

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
MERCURO	 <b>CSP</b>	MERCSP	 Z87 +U6 L1.5	 ANSI Z87.1+	Anti-scratch/Anti-fog 
	 Smoke	MERPSF	 Z87 +U6 L3	 ANSI Z87.1+	Anti-scratch/Anti-fog 
	 <b>POLARIZED</b>	MERPOL	 Z87 +U6 L3	 ANSI Z87.1+	AS
	Retainer strap (option)	UNIVSTRAP	-	-	-

### LENS MARKING

- **Crown** = Manufacturer Mark
- **Z87+** = Impact rated for Plano product - tested and approved to ANSI Z81.1-2015
- **Lens type**
  - Clear = none
  - Welding = W and Shade number from 1,3 to 14
  - UV filter = U and scale number from 2 to 6
  - Visible light filter = L and scale number from 1,3 to 10
  - IR filter = R and scale number from 1n3 to 10
  - Variable tint = V
  - Special purpose = S

 **WARNING:** Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNOLOGIES

#### CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.



This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd/m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes. The PLATINUM lens innovation improves eye protection.

### FRAME MARKING

- **Crown** = Manufacturer Mark
- **Z87+** = Impact rated for Plano product - tested and approved to ANSI Z81.1-2015
  - Splash/droplet protection = D3
  - Nuisance Dust protection = D4
  - Fine Dust protection = D5
- **Country of origin** = Taiwan

**ANSI:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Maximum protection for glasses. Use for high speed particles at extreme temperatures.

**Bollé Safety product approval certificates to ANSI standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the glasses or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE				
	MERCSP	MERPSF	MERPOL	RUSHKITS
Individual plastic bag	3660740008901	3660740008895	3660740008888	3660740007546
10 safety spectacles per inner box	3660740108908	3660740108892	3660740108885	3660740107543
200 safety spectacles per outer pack (240 for MERPOL)	3660740208905	3660740208899	3660740208882	3660740207540

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
BRIDGE	PVC



Non-contractual pictures

01/2021

Bollé Safety USA  
2810 Caribou Court, Suite 160  
Carlsbad, CA 92010  
[salesUSA@bolle-safety.com](mailto:salesUSA@bolle-safety.com)

[bollesafety-usa.com](http://bollesafety-usa.com)

**bolle**  
SAFETY