

COVERSAL

PROTECTION & EFFICIENCY

Thanks to its polycarbonate inner lenses, this model offers effective twin protection against gas welding rays and solid projectiles

 125 G

- + ADJUSTABLE STRAP
- + FITS OVER PRESCRIPTION SPECTACLES
- + INTERCHANGEABLE LENSES



TECHNOLOGIES





CSP

VERSIONS



COVRP5

COVERSAL

VERSION	REFERENCE	LENS MARKING	FRAME MARKING	COATING	STANDARD
 WELDING 5 VENTED - INDIRECT VENTILATION	 COVRP5	5  1 C €	 EN166 / EN175 F C €		EN166-EN175

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO C € STANDARDS WILL BE SENT ON REQUEST.

PACKAGING & EAN13 CODE

SINGLE:	INNER BOX:	OUTER PACK:
Size: 32 x 15 x 5 mm	Size: 24x18x9 cm Weight: 0.84 kg	Size: 60 x 50 x 38 cm Weight: 18.22 kg
3660740001063	3660740101060 - 5 pcs	3660740201067 - 120 pcs
CUSTOM CODE: 9004909000		

GENERAL SPECIFICATIONS

LENS	POLYCARBONATE - 1.5 MM	FRAME	PVC
CURVE	4 - SLIGHTLY CURVED	STRAP	NYLON POLYESTER - 160MM



CLEANING & STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



MADE IN: TW

DATASHEET: 03-29-2022

bolle-safety.com

Europe Headquarters
 34 rue de la Soie
 69100 Villeurbanne
 France
 P : 00 33 (0) 4 78 85 23 64

U.K. & Ireland
 Unit C83 - Barwell Business Park
 Leatherhead Road - Chessington
 Surrey - KT9 2NY - UK
 P : 00 44 (0)208 391 4700

USA Office
 2810 Caribou Court, Suite 160
 Carlsbad, CA 92010
 United States of America
 P : 800 222 6553

Asia-Pacific Office
 32-40 Fairchild Street
 Heatherton VIC 3202
 Australia
 P : 1300 138 098

