

HUSTLER SEAL



1662601 : Clear Lens



1662602 : Smoke Lens



1662607 : Green Polarised



EVA fitted seal
for maximum
protection

 **PLATINUM**



33 g

+ PLATINUM COATING (P)

+ MEDIUM - LARGE FIT

+ EVA FITTED SEAL TO MAXIMISE








PROTECTION IN DUSTY ENVIRONMENTS.

+ RUBBER NOSE PADS FOR NON SLIP FIT


+ HIGH GLOSS BLACK NYLON FRAME

bolle
SAFETY

HUSTLER SEAL

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
HUSTLER SEAL	 Clear	1662601	IO & 	AS/NZS 1337.2010	Anti-scratch/Anti-fog/Platinum [®] 
	 Smoke	1662602	I3 & 	AS/NZS 1337.2010	Anti-scratch/Anti-fog/Platinum [®] 
	 Grey Green Polarised	1662607	I3	AS/NZS 1337.2010	Anti-scratch/Anti-fog

LENS MARKING

 Platinum is a permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 -88% (twilight).
- 3. Range of luminous transmittance 8 -18% (smoke & polarised).

APPLICATIONS

- High dust work environments
- Solar UV exposure
- Emergency response
- Rigging
- Assembly and production work
- High glare outdoor work places
- Driving


MAIN MARKETS

- Mining
- Construction
- Local government and councils
- Utilities: power, gas and water
- Fisheries
- Transport

LENSES

- 2mm polycarbonate
- 8 base curve
- New Platinum Coating - A high performance anti-fog + anti-scratch coating system applied on both sides of Clear and Smoke lenses
- 100% UV 385 – Clear

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our  Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Yes
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz