

# TG12

## FOR HEALTHCARE PROFESSIONALS

**TG12** is a pair of over-the-glasses **accessible to all**. Simple and economical, TG12 model helps to reduce workplace accidents. Equipped with **anti-fog coating**, TG12 ensures long-lasting comfort and reliability. Compatible with most prescription glasses. Suitable for healthcare industry.









PSOTG12009

  
35 g



- + **WIDE FIELD OF VIEW**
- + **SINGLE LENS FRAME FOR BETTER VISION**
- + **ANTI-FOG COATING**
- + **WIDE TEMPLES FOR BETTER PROTECTION**
- + **FITS OVER PRESCRIPTION GLASSES**
- + **FITS ALL FACES**

# TG12

MODEL	VERSIONS	REFERENCES	LENS MARKINGS	FRAME MARKINGS	COATINGS
<b>TG12</b>	 Clear	PSOTG12009	2C-1.2  1 FT  	 	AF

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

Always read and follow the instructions on the label.

## FRAME MARKINGS

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**Z87+ :** Impact rated for Plano product - tested and approved to ANSI Z81.1-2015

**AS/NZS 1337.1:2010 :** Tested & approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm ball at 45 m/s.

### Others symbols:

 European standard

 Manufacturer's markings

Made in China

## LENS MARKINGS

### Optical class symbols:

**1.** Continuous work

**U6.** UV filter: U and scale number from 2 to 6

**O.** Range of luminous transmittance 80-100% (clear)

### Mechanical strength symbols:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**I.** The letter «I» signifies «Medium Impact» approval.

### Others symbols:

 European standard

 Manufacturer's markings

**Z87+ :** Impact rated for Plano product - tested and approved to ANSI Z81.1-2015

**O.** Range of luminous transmittance 80-100% (clear)

## PACKAGING AND EAN13 CODE

	PSOTG12009
Individual plastic bag	3660740011178
Inner box (10 products)	3660740101176
Outer pack (20 boxes/200 products)	3660740201173
Outer pack size : 61 x 28 x 82cm Outer pack G.W : 11.4 Kg	

## CARACTERISTICS

LENS	PC - 2 mm - Curve 4
FRAME	PC
TEMPLES	PC
SPARE LENS	No

Non-contractual pictures  
26/05/2021

### ASIA/PACIFIC HEADQUARTERS:

Bollé Safety AU Pty Limited  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: sales@bollesafety.com.au

[bollesafety.com.au](http://bollesafety.com.au)

### NEW ZEALAND:

T.: 0800 2655 369  
E: sales@bollesafety.com.au

**bolle**  
SAFETY