

MY6 EYESHIELD

ADAPTABILITY & PERFORMANCE

Experience unmatched performance with MY6, the ultimate ballistic eyeshield designed for mission-critical scenarios. Crafted with precision, it integrates advanced features to enhance your performance and ensure optimal visual clarity, comfort and style. Our exclusive PLATINUM technology guarantees a clear line of sight, even in challenging environments, while its superior ballistic impact resistance allows MY6 to withstand even the most extreme situations. Tailor your eyeshield to your preferences with our diverse range of CSP lens tint options, empowering you to make precise decisions with unwavering confidence. MY6 offers a secure and comfortable fit, enabling agile and assured movements during any operation. While your team relies on you to watch their backs, trust us to safeguard your eyes every step of the way.

SUPPLIED WITH : KIT (Box, case, microfiber pouch, user instruction)

 37 G

- +
HIGH-IMPACT BALLISTIC PROTECTION: MIL & STANAG
- +
PLATINUM COATING : ANTI-SCRATCH & ANTI-FOG
- +
NON-SLIP ADJUSTABLE NOSE BRIDGE
- +
THIN AND COMFORTABLE TEMPLES COMPATIBLE WITH COMMUNICATIONS SYSTEMS AND BALLISTIC HELMETS



TECHNOLOGIES

CSP

PLATINUM

PROLASER

VERSIONS

 MY6EST10W	 MY6EST70W	 MY6EST00W
 MY6EST20W	 MY6EST71W	 MY6EST02W
 MY6EST30W	 MY6EST72W	 MY6EST01W
 MY6EST31W	 MY6EST73W	 MY6EST03W
 MY6EST32W	 MY6EST05W	 MY6EST04W
 MY6EST10W	 MY6EST07W	 MY6EST09W
 MY6EST20W	 MY6EST08W	 STRAPT00W



MY6 EYESHIELD						
REFERENCE	VERSION	LENS MARKING	FRAME MARKING	BALLISTIC RESISTANCE V50 STANAG 2920	MIL-PRF	COATING
MY6EST10W	CLEAR	2C-1.2 1 FT KN CE	EN166 FT CE CE	221,3 M/S	32432A	PLATINUM
MY6EST20W	SMOKE	5-3.1 1 FT KN CE	EN166 FT CE CE	226,6 M/S	32432A	PLATINUM
MY6EST30W	COPPER	5-1.4 1 FT KN CE	EN166 FT CE CE	219,7 M/S	32432A	PLATINUM
MY6EST31W	AMBER	2C-1.2 1 FT KN CE	EN166 FT CE CE	226,5 M/S	32432A	PLATINUM
MY6EST32W	VERMILLON	5-2 1 FT KN CE	EN166 FT CE CE	238,8 M/S	32432A	PLATINUM
MY6EST70W	CLEAR COPPER	CLEAR : 2C-1.2 1 FT KN CE COPPER : 5-1.4 1 FT KN CE	EN166 FT CE CE	CLEAR : 221,3 M/S COPPER : 219,7 M/S	32432A	PLATINUM
MY6EST71W	CLEAR SMOKE	CLEAR : 2C-1.2 1 FT KN CE SMOKE : 5-3.1 1 FT KN CE	EN166 FT CE CE	CLEAR : 221,3 M/S SMOKE : 226,6 M/S	32432A	PLATINUM
MY6EST72W	CLEAR COPPER SMOKE	CLEAR : 2C-1.2 1 FT KN CE COPPER : 5-1.4 1 FT KN CE SMOKE : 5-3.1 1 FT KN CE	EN166 FT CE CE CE	CLEAR : 221,3 M/S COPPER : 219,7 M/S SMOKE : 226,6 M/S	32432A	PLATINUM
MY6EST73W	CLEAR COPPER SMOKE	CLEAR : 2C-1.2 1 FT KN CE COPPER : 5-1.4 1 FT KN CE SMOKE : 5-3.1 1 FT KN CE	EN166 FT CE CE CE	CLEAR : 221,3 M/S COPPER : 219,7 M/S SMOKE : 226,6 M/S	32432A	PLATINUM
SPARE LENSES	MY6EST00W	CLEAR	2C-1.2 1 FT KN CE	221,3 M/S	32432A	PLATINUM
	MY6EST01W	COPPER	5-1.4 1 FT KN CE	226,6 M/S	32432A	PLATINUM
	MY6EST02W	SMOKE	5-3.1 1 FT KN CE	226,5 M/S	32432A	PLATINUM
	MY6EST03W	AMBER	2C-1.2 1 FT KN CE	219,7 M/S	32432A	PLATINUM
	MY6EST04W	VERMILLON	5-2 1 FT KN CE	238,8 M/S	32432A	PLATINUM
MY6 PROLASER						
MY6EST90W	PROLASER EMERALD	405/694/1064NM - OD4	EN166 FT CE CE	218,3 M/S	32432A	
MY6EST91W	PROLASER TOPAZ	405/445/532NM - OD4	EN166 FT CE CE	226,6 M/S	32432A	

BALLISTIC STANDARDS			
STANAG <i>2920</i>		MIL-PRF <i>32432A</i>	
GENERAL SPECIFICATIONS			
LENS	POLYCARBONATE - 2.7MM - CURVE 7	CE	EN166
FRAME	NYLON/PC/TPR - HALF FRAME	ANSI	ANSI Z87.1-2020
STRAP	STRAPT00W	AS/NZS	AS/NZS 1337.1:2010
MADE IN	TW	DATASHEET	11-03-2025

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO CE STANDARDS WILL BE SENT ON REQUEST.

***MADE TO ORDER:** minimum order quantity applicable

bolle-safety.com

Europe Headquarters
34 rue de la Soie
69100 Villeurbanne
France
Tél. : 00 33 (0) 4 78 85 23 64

U.K. & Ireland
Unit C83-Barwell Business Park
Leatherhead Road-Chessington
Surrey-KT9 2NY-UK
Tél. : 00 44 (0)208 391 4700

USA Office
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
United States of America
Tél. : 800 222 6553

Asia-Pacific Office
32-40 Fairchild Street
heatherton VIC 3202
Australia
Tél. : 1300 138 098



PACKAGING & EAN13 CODE		
SINGLE: Size: 18.5 x 7.3 x 7.3 cm	INNER BOX: Size: 27 x 15.4 x 5.2cm Weight: 0.25 kg	OUTER PACK: Size: 58 x 30 x 21 cm Weight: 3.82 kg
3660740019068		3660740219062
3660740019082		3660740219086
3660740019075		3660740219079
3660740019099		3660740219093
3660740019105		3660740219109
3660740019037		3660740219031
3660740019044		3660740219048
3660740019051		3660740219055
3660740019181		3660740219185
3660740019112	3660740119119	3660740219116
3660740019129	3660740119126	3660740219123
3660740019136	3660740119133	3660740219130
3660740019143	3660740119140	3660740219147
3660740019150	3660740119157	3660740219154
PACKAGING & EAN13 CODE		
3660740019181		3660740219185
3660740019198		3660740219192
CUSTOM CODE: 9004901000		

OPTIONAL ACCESSORIES				
REFERENCE	DESCRIPTION	SINGLE	INNER BOX	OUTER PACK
MY6EST05W	BLACK SPARE NOSE PIECE	3660740019167	3660740119164	3660740219161
MY6EST07W	BLACK RX CONNECTOR NOSE PIECE SLOT CONNECTION UPLC	3660740020668	3660740120665	3660740220662
MY6EST08W	BLACK RX CONNECTOR NOSE PIECE CLIP CONNECTION	3660740020675	3660740120672	3660740220679
MY6EST09W	PANORAMIC RX CARRIER PC CLEAR - CLIP CONNECTION	3660740022068	3660740122065	3660740222062
STRAPT00W	STRAP BLACK FIRE - RETARDANT	3660740019594	3660740119591	3660740219598

KNOW MORE ABOUT MARKINGS:

OR SCAN:

CLEANING & STORAGE
CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.
MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the glasses or goggles in a microfiber pouch or rigid case.
STORAGE : All products must be stored in a dry and clean environment.

