OVERLIGHT

OTG

OVERLIGHT is the new generation of OTG (over the glasses). Highly wrap-around and attractive, they guarantee maximum safety for all, including wearers of prescription glasses.

NEW VERSION 1 SIZE



OVLITLPSI

33 g

- + HIGHLY WRAP-AROUND FRAME
- + SIDE, UPPER AND LOWER PROTECTION
- + DESIGN



OVERLIGHT

OTG

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|-----------|----------|------------|------------------|-----------------------------|-----------------------|
| OVERLIGHT | Clear | OVLITLPSI | 2C-1,2 😭 1 FT C€ | ≌ EN166 FT C€ | Anti-scratch/anti-fog |

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

| PACKAGING AND EAN13 CODE | | | | |
|--|---------------|--|--|--|
| | OVLITLPSI | | | |
| Individual plastic bag | 3660740006495 | | | |
| 10 safety spectacles per box | 3660740106492 | | | |
| 180 safety spectacles per outer pack | 3660740206499 | | | |

| CHARACTERISTICS | | | | |
|-----------------|--------------------------|--|--|--|
| LENSES | PC - 2,4 mm - Curve 2.75 | | | |
| FRAME | PC | | | |
| TEMPLES | PC | | | |
| STRAP | Non applicable | | | |
| FOAM | Non applicable | | | |
| SPARE LENSES | No | | | |











02/05/2016

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

