

BL15

B-LINE is a range of safety eyewear **accessible to all** and is adapted to the most common industrial risks. **B-LINE** benefits from Bollé Safety's expertise and quality.

Simple and economic, BL15 goggles fit to all and can be worn over glasses.

B LINE




BL15API
(Vented)



BL15APSI
(Vented)



PSGBL15-A02
(Sealed)



2.72 oz










Vented versions

Sealed version

- + CLEAR TRANSLUCENT FRAME
- + SEALED OR VENTED VERSIONS
- + AVAILABLE WITH ANTI-FOG & ASAF COATINGS
- + ADJUSTABLE STRAP
- + FITS OVER PRESCRIPTION GLASSES

bollé
SAFETY

BL15

MODEL	VERSIONS	REFERENCES	LENS MARKINGS	FRAME MARKINGS	COATINGS
BL15	 Clear Vented	BL15API	 Z87+	 Z87+ D3/D4	-
	 Clear Vented	BL15APSI	 Z87+	 Z87+ D3/D4	AF
	 Clear Sealed	PSGBL15-A02	 Z87+	 Z87+ D3/D4/D5	ASAF

LENS MARKINGS

- **Crown** = Manufacturer Mark
- **Z87+** = Impact rated for Plano product - tested and approved to ANSI Z81.1-2015
- **Lens type**
 - Clear = none
 - Welding = W and Shade number from 1,3 to 14
 - UV filter = U and scale number from 2 to 6
 - Visible light filter = L and scale number from 1,3 to 10
 - IR filter = R and scale number from 1n3 to 10
 - Variable tint = V
 - Special purpose = S

FRAME MARKINGS

- **Crown** = Manufacturer Mark
- **Z87+** = Impact rated for Plano product - tested and approved to ANSI Z81.1-2015
 - Splash/droplet protection = D3
 - Nuisance Dust protection = D4
 - Fine Dust protection = D5
- **Country of origin** = Taiwan

ANSI: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Maximum protection for glasses. Use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to ANSI standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the glasses or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

	BL15API	BL15APSI	PSGBL15-A02
Individual plastic bag	3660740003036	3660740003043	3660740010430
180 safety goggles per outer pack	3660740203030	3660740203047	3660740200435

CARACTERISTICS

LENS	PC - 2 mm - Curve 4
FRAME	PVC
STRAP	Polyester
SPARE LENS	No



09/01/2021

Bollé Safety-USA
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
USA

bollesafety-usa.com

bolle
SAFETY