

# TG12

**TG12** is a pair of over-the-glasses **accessible to all**. Simple and economic, TG12 fits to all and can be worn over glasses.








35 g



PSOTG12009

- + WIDE FIELD OF VIEW**
- + SINGLE LENS FRAME FOR A BETTER VISION**
- + ANTI-FOG COATING**
- + WIDE TEMPLES FOR A BETTER PROTECTION**
- + FITS OVER PRESCRIPTION GLASSES**
- + FITS ALL FACES**

# TG12

MODEL	VERSIONS	REFERENCES	LENS MARKINGS	FRAME MARKINGS	COATINGS
<b>TG12</b>	 Clear	PSOTG12009	2C-1.2  1 FT  Z87+U6 I0	 EN166 FT  Z87+ MADE IN CHINA AS/NZS 1337.1:2010	AF

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

## FRAME MARKINGS

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**Z87+ :** Impact rated for Plano product - tested and approved to ANSI Z81.1-2015

**AS/NZS 1337.1:2010 :** Tested & approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

### Others symbols:

 European standard

 Manufacturer's markings

Made in China

## LENS MARKINGS

### Optical class symbols:

**1.** Continuous work

**U6.** UV filter: U and scale number from 2 to 6

**0.** Range of luminous transmittance 80-100% (clear)

### Mechanical strength symbols:


**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**I.** The letter «I» signifies «Medium Impact» approval.

### Others symbols:

 European standard

 Manufacturer's markings

**Z87+ :** Impact rated for Plano product - tested and approved to ANSI Z81.1-2015

**0.** Range of luminous transmittance 80-100% (clear)

## PACKAGING AND EAN13 CODE

	PSOTG12009
Individual plastic bag	3660740011178
Inner box (10 products)	3660740101176
Outer pack (20 boxes/200 products)	3660740201173
Outer pack size : 61 x 28 x 82cm Outer pack G.W : 11.4 Kg	

## CARACTERISTICS

LENS	PC - 2 mm - Curve 4
FRAME	PC
TEMPLES	PC
SPARE LENS	No
PROTECTION	PPE CAT. 2

01/05/2020

EMEA  
Bollé Safety  
34 rue de la Soie  
69100 Villeurbanne  
France

[bolle-safety.com](http://bolle-safety.com)

**bolle**  
SAFETY