

TRYON

bolle
SAFETY
STANDARD ISSUE

FRAME

- + WRAPAROUND
- + ADJUSTABLE FLEX NOSE BRIDGE
- + SINGLE-LENS FRAME



TEMPLES

- + BI-MATERIAL PC/TPR
- + FLEX 160° TEMPLES
- + STRAP KIT (OPTION)

LENS

- + PLATINUM® ASAF COATING
- + WIDE FIELD OF VISION



CLEAR
#PSSTRY0064



SMOKE
#PSSTRY0443



CSP
#PSSTRY0C13



FLASH
#PSSTRY0F12



POLARIZED
#PSSTRY0P11



STRAP
#UNIVSTRAP

1.24 oz

+ MICROFIBER POUCH INCLUDED

VERSIONS

DESCRIPTION

Wraparound, equipped with co-injected FLEX160° temples, an adjustable nose bridge, and our exclusive PLATINUM® ASAF coating...TRYON perfectly combines innovation and absolute protection.

PLATINUM® (P) ASAF Coating

Permanent coating on both sides of the lens gives them a high resistance to scratching, and delays the onset of fogging. Certified K & N (EN166) PLATINUM® resists to the most aggressive chemicals.

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

TECHNOLOGIES



TRYON

bolle
SAFETY
STANDARD ISSUE

MODEL	FRAME	VERSIONS	REFERENCES	LENS MARKINGS	FRAME MARKINGS	V50 BALISTIC RESISTANCE STANAG 2920	ANSI/MIL	COATING
TRYON	■ Matte black	Clear	PSSTRYO064	☞ Z87+ U6	☞ Z87+	-	-	ASAF
	■ Matte black	Smoke	PSSTRYO443	☞ Z87+ U6 L3	☞ Z87+	-	-	ASAF
	■ Matte black	CSP	PSSTRYOC13	☞ Z87+ U6 L1.5	☞ Z87+	-	-	ASAF
	■ Matte black	Blue Flash	PSSTRYOF12	☞ Z87+ U6 L3	☞ Z87+	-	-	AS
	■ Matte black	Polarized	PSSTRYOP11	☞ Z87+ U6 L3	☞ Z87+	-	-	AS
	Strap Kit	-	UNIVSTRAP	-	-	-	-	-

Lens markings

Z87+. Impact rated for Plano product - tested and approved to ANSI Z87.1-2015

☞ Manufacturer name

Lens Type:

Clear = none

Welding = W and Shade number from 1,3 to 14

UV filter = U and scale number from 2 to 6

Visible light filter = L and scale number from 1,3 to 10

IR filter = R and scale number from 1,3 to 10

Variable tint = V

Special purpose = S

Frame markings

☞ Manufacturer name

Country of Origin: Taiwan

Z87+. Impact rated for Plano product - tested and approved to ANSI Z87.1-2015

Mechanical strength symbols:

ANSI. guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc. Maximum protection for glasses. Use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to ANSI standards will be sent on request.

	PSSTRYO064	PSSTRYO443	PSSTRYOC13	PSSTRYOF12	PSSTRYOP11	UNIVSTRAP
EAN13 Unit pack	3660740010904	3660740010928	3660740010911	3660740010935	3660740011611	3660740007546
EAN13 Inner pack (number of unit per inner pack)	3660740110901 (10 units)	3660740110925 (10 units)	3660740110918 (10 units)	3660740110932 (10 units)	3660740111618 (10 units)	3660740107543 (40 units)
Size // Weight Inner pack	24x18x9 cm 0.47 kg	24x18x9 cm 0.47 kg	24x18x9 cm 0.47 kg	24x18x9 cm 0.47 kg	24x18x9 cm 0.47 kg	28x16x7 cm 0.61 kg
EAN13 Carton (number of unit per master pack)	3660740210908 (200 units)	3660740210922 (200 units)	3660740210915 (200 units)	3660740210939 (240 units)	3660740211615 (240 units)	3660740207540 (480 units)
Size // Weight Master pack	60x50x37 cm 11.60 kg	60x50x37 cm 11.60 kg	60x50x37 cm 11.60 kg	60x50x37 cm 13.10 kg	60x50x37 cm 13.10 kg	46x37x28 cm 7.30 kg

Maintenance: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

Storage: All products must be stored in a dry and clean environment.

TRYON	
Lens	PC - 2.2 mm - Curve 8
Temples	PC + TPR
Strap	Nylon - 15mm
Frame	PC + TPR
Spare lens	No
Country of origin	Taiwan



For more information on this product and the BSSI range, visit:

bollesafety-usa.com

BOLLÉ SAFETY
1896 Rutherford Rd
Carlsbad, CA 92008
USA