

PILOT

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

Its co-injected, ventilated frame guarantees unequalled adaptability and comfort.

 PLATINUM



3.1 oz



40274









40275

- + EXCELLENT FIELD OF VISION**
- + RATED D3/D4 FOR PROTECTION FROM SPLASH AND DUST**
- +  PLATINUM ANTI-FOG & ANTI-SCRATCH COATING (P)**
- + ADJUSTABLE STRAP**
- + PP/TPR TWIN-MATERIAL FRAME**
- + FITS OVER PRESCRIPTION GLASSES**

bolle
SAFETY

PILOT

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|-------|--|------------|--|--|---------------------------|
| PILOT |  Vented | 40274 |  Z87+ U6 |  Z87+ D3/D4 | Anti-scratch/anti-fog (☑) |
| |  Vented CSP | 40275 |  Z87+ U6S |  Z87+ D3/D4 | Anti-scratch/anti-fog (☑) |

LENS MARKING

- **Crown** = Manufacturer Mark
- **Z87+** = Impact rated for Plano product - tested and approved to ANSI Z81.1-2015
- **Lens type**
 - Clear = none
 - Welding = W and Shade number from 1,3 to 14
 - UV filter = U and scale number from 2 to 6
 - Visible light filter = L and scale number from 1,3 to 10
 - IR filter = R and scale number from 1n3 to 10
 - Variable tint = V
 - Special purpose = S

⚠ **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov

TECHNOLOGIES

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

PLATINUM®

The exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

| PACKAGING AND EAN13 CODE | | |
|-----------------------------------|--------------|--------------|
| | 40274 | 40275 |
| Individual plastic bag | 054917326869 | 054917326890 |
| 5 safety goggles per inner box | 054917326869 | 054917326890 |
| 120 safety goggles per outer pack | 054917326869 | 054917326890 |



Bollé Safety-USA
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
USA

bollesafety-usa.com

FRAME MARKING

- **Crown** = Manufacturer Mark
- **Z87+** = Impact rated for Plano product - tested and approved to ANSI Z81.1-2015
 - Splash/droplet protection = D3
 - Nuisance Dust protection = D4
 - Fine Dust protection = D5
- **Country of origin** = Taiwan

ANSI: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Maximum protection for glasses. Use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to ANSI standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the glasses or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

| CHARACTERISTICS | |
|-----------------|-------------------------|
| LENSES | PC - 2,1 mm - Curve 5,5 |
| FRAME | PP + TPR |
| TEMPLES | Non applicable |
| STRAP | Nylon |
| FOAM | No |
| SPARE LENSES | No |

04/01/2021

bolle
SAFETY