



# X1000

## RESISTANCE & COMFORT

The newest generation of low profile ballistic goggles, the X1000 goggle adapts to your every need. X1000 has a choice of interchangeable lenses for all use. It is perfectly suited for use while wearing a helmet, offering comfort, adaptability and protection. The X1000 is the ideal goggle for extreme situations.

**SUPPLIED WITH :** Microfiber pouch - case

106 G

- + PANORAMIC FIELD OF VISION
- + PIVOT FOR HELMET WEARERS - QUICK RELEASE SYSTEM
- + HIGH-TEMPERATURE RESISTANT TPV VENTILATED FRAME
- + PLATINUM COATING : ANTI-SCRATCH & ANTI-FOG



### TECHNOLOGIES

CSP  
PLATINUM

### VERSIONS



X1NSTDI





## X1000

| REFERENCE | VERSION | LENS MARKING        | FRAME MARKING   | BALLISTIC RESISTANCE V50 STANAG 2920 | MCEPS       | COATING  |
|-----------|---------|---------------------|-----------------|--------------------------------------|-------------|----------|
| X1NSTDI   | CLEAR   | 2C-1.2 ☞ 1 BT KN C€ | ☞ EN166 3 BT C€ | 795 KM/H - 220.7 M/S                 | GL-PD-10-12 | PLATINUM |
| FAX1STDJ  | AMBER   | 2C-1.2 ☞ 1 BT KN C€ |                 | 774 KM/H - 215.7 M/S                 | GL-PD-10-12 | PLATINUM |
| FAX1STDF  | SMOKE   | 5-2.5 ☞ 1 BT KN C€  |                 | 782 KM/H - 217.2 M/S                 | GL-PD-10-12 | PLATINUM |

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO C€ STANDARDS WILL BE SENT ON REQUEST.

## PACKAGING &amp; EAN13 CODE

| SINGLE:<br>Size: 10 x 9 x 19 | INNER BOX:<br>NOT AVAILABLE | OUTER PACK:<br>Size: 60 x 50 x 38 cm<br>Weight: 17.9 kg |
|------------------------------|-----------------------------|---|
| 3660740005108                | -                           | 3 660 740 205 102 - 60 pcs                              |
| 3660740005245                | 3 660 740 105 242 - 15 pcs  | 3 660 740 205 249 - 150 pcs                             |
| 3660740005238                | 3 660 740 105 235 - 15 pcs  | 3 660 740 205 232 - 150 pcs                             |
| CUSTOM CODE: 9004901000      |                             |   |

## BALLISTIC STANDARDS

**STANAG  
2920**

**MCEPS  
GL-PD-10-12**

## OPTIONAL ACCESSORIES

| REFERENCE | DESCRIPTION | SINGLE:       | INNER BOX:        | OUTER PACK:       |
|-----------|-------------|---------------|-------------------|-------------------|
| SOSX1000  | RX INSERT   | 3660740000721 | 3 660 740 100 728 | 3 660 740 200 725 |

## GENERAL SPECIFICATIONS

|       |                               |        |                 |
|-------|-------------------------------|--------|-----------------|
| LENS  | POLYCARBONATE - 3MM - CURVE 5 | C€     | EN166 - EN170   |
| FRAME | TPV - SANTOPRENE - VENTED     | ANSI   | ANSI Z87.1-2010 |
| STRAP | NYLON POLYESTER               | AS/NZS |                 |

KNOW MORE  
ABOUT  
MARKINGS:



OR SCAN:

## CLEANING &amp; STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bolle Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.



MADE IN: TW

DATASHEET: 02-25-2022

**bolle-safety.com**

Europe Headquarters  
34 rue de la Soie  
69100 Villeurbanne  
France  
Tél. : 00 33 (0) 4 78 85 23 64

U.K. & Ireland  
Unit C83 - Barwell Business Park  
Leatherhead Road - Chessington  
Surrey - KT9 2NY - UK  
Tél. : 00 44 (0)208 391 4700

USA Office  
2810 Caribou Court, Suite 160  
Carlsbad, CA 92010  
United States of America  
Tél. : 800 222 6553

Asia-Pacific Office  
32-40 Fairchild Street  
heatherton VIC 3202  
Australia  
Tél. : 1300 138 098

