

COBRA TPR

FOR CLEAN ENVIRONMENTS AND EXTREME CONDITIONS

With its easy-to-clean neoprene strap and its built-in TPR foam, this goggle is especially suitable for offshore/oil & gas industries.

 PLATINUM®




34 g

SUPPLIED WITH

Microfibre pouch
ETUIFS







COBTTPRPSI

- + HIGH STRENGTH GOGGLE
- + NEOPRENE STRAP AND TPR COMFORT FOAM
- +  PLATINUM® (+P) COATING
- + COMPACT, LIGHTWEIGHT AND PANORAMIC
- + 100% SEALED

bolle
SAFETY

COBRA TPR

FOR CLEAN ENVIRONMENTS AND EXTREME CONDITIONS

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|-----------------------------------|---|------------|---|---|---|
| COBRA TPR Sealed goggle |  Clear | COBTPRPSI | 2C-1.2  1 BT KN C€ |  EN166 3 4 5 BT C€ | Anti-scratch/Anti-fog () |

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:


B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

C€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.


3. Liquid droplets or splashes.

4. Large dust particles > 5 microns.

5. Gas and fine dust particles < 5 microns.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

PLATINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching, to the most aggressive chemicals and delays the onset of fogging.

In all circumstances and at all times the PLATINUM® lens innovation guarantees your eyes improved protection.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

| CHARACTERISTICS | |
|-----------------|----------------------------|
| LENSES | PC - 2,2 mm - Curve 9 |
| STRAP | 15mm adjustable - Isoprene |
| FOAM | TPR |

| PACKAGING AND EAN 13 CODE | |
|-----------------------------------|---------------|
| | COBTPRPSI |
| Individual plastic bag | 3660740007522 |
| 10 safety goggles per box | 3660740107529 |
| 240 safety goggles per outer pack | 3660740207526 |



19/07/2016

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY