

TRYON RX

STYLE AND PERFORMANCE

CR39 and Polycarbonate lenses available.

★ EXCELLENCE
A concentrate of innovation
for greater comfort,
performance and style



TRYON



34 g

SUPPLIED WITH	FRAME	LENS MATERIAL AVAILABLE	OPTIONAL
Hard case, microfibre cloth, cord	• PC/TPR	• CR39 • Polycarbonate	Retainer strap Ref. RUSHKITS



- + WRAP-AROUND FRAME
- + CO-INJECTED PC/TPR TEMPLES
- + NON-SLIP ADJUSTABLE BRIDGE
- + FLEX 160° TEMPLES

bolle
SAFETY

TRYON RX

STYLE AND PERFORMANCE

MODEL	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
TRYON RX	TRYON	53/18	EN166 F C€	135 mm
Strap only (option)	RUSHKITS	-	-	-

LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.


CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

FRAME MARKING

EN 166 : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

C€ European standard  Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power: +5,5/-8

Maximum cylinder compared with sphere : +/-5.

CORRECTED BASE:

Corrected base : 8

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE		
	TRYON	RUSHKITS
Per piece	3660740008291	3660740007546

CHARACTERISTICS	
LENS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Free form - Degressive
FRAME	PC/TPR
STRAP	Nylon/15mm/Adjustable



Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

13/06/2017

bolle
SAFETY