

B713

ELEGANCE AND PROTECTION



Size S: 38g | Size L: 40g

SUPPLIED WITH

Hard case,
microfibre cloth,
cord



FRAME

- Metal
- Acetate Temples
- Wire core Temples

LENS MATERIAL AVAILABLE

- CR39
- Polycarbonate

Size S



Ref. B713S

Size L



Ref. B713L

- + ACETATE TEMPLES
- + IN-BUILT SIDE SHIELDS
- + NON-SLIP INSERTS
- + WIRE CORE TEMPLES

bolle
SAFETY

B713

ELEGANCE AND PROTECTION

MODEL	VERSIONS	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
B713	S - Light grey side shields	B713S	52/17	EN166 F CE	135 mm
	L - Light grey side shields	B713L	54/17	EN166 F CE	135 mm

LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.


CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

FRAME MARKING

EN 166 : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

CE European standard  Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power:

Excellence +10/-10

Maximum cylinder compared with sphere : +/-6.

CORRECTED BASE:

Corrected base : 4

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE		
	B713S	B713L
Per piece	3660740008093	3660740008109

CHARACTERISTICS	
LENS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision, Freeform single vision, Progressive, Freeform Progressive, Degressive, Bifocal
FRAME	Metal / Chocolate
STRAP	Non applicable
FOAM	Non applicable



Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

06/12/2016

bolle
SAFETY