

BAXTER RX

COMFORT AND INGENUITY

BAXTER RX, the alternative to the TWISTER model, offers total comfort thanks to its highly wrap-around frame. With its waterproof foam and ingenious system for attaching the strap, BAXTER RX offers effective protection from sprays of solids and liquids, and from dust. CR39 and Polycarbonate lenses available.



★ EXCELLENCE
A concentrate of innovation
for greater comfort,
performance and style



49 g

SUPPLIED WITH

Hard case,
microfibre cloth,
cord



FRAME

• TR90

LENS MATERIAL AVAILABLE

• CR39
• Polycarbonate

SUPPLIED WITH / OPTION

Foam and strap



BAXN

- + INCREASED PROTECTION
- + WRAP-AROUND FRAME
- + WATERPROOF FOAM AND REMOVABLE STRAP

bollé
SAFETY

BAXTER RX

COMFORT AND INGENUITY

MODEL	VERSIONS	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
BAXTER RX Spectacles version	Worn as spectacles	BAXN	63/18	☞ EN166 F ☞	122 mm
BAXTER RX Strap version	Foam + strap only kit	BAXKITFS	-	☞ EN166 3 4 5 B ☞	-
	Worn with foam + strap	-	-	☞ EN166 3 4 5 B ☞	-

LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power: +5,5/-8

Maximum cylinder compared with sphere : +/-5.

CORRECTED BASE:

Corrected base : 8

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets.

4. Large dust particles > 5 microns.

5. Gas and fine dust particles < 5 microns.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

☞ European standard ☞ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE		
	BAXN	BAXKITFS
Individual plastic bag	3660740008314	3660740008000

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	TR90
TEMPLES	TR90
STRAP	Nylon
FOAM	PC + EVA



13/07/2017

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY