

HUSTLER RX

DESIGN AT THE SERVICE OF PROTECTION

CR39 and Polycarbonate lenses available.

★ EXCELLENCE
A concentrate of innovation
for greater comfort,
performance and style



32g



HUSTN

SUPPLIED WITH

Hard case,
microfibre cloth,
cord



FRAME

- Nylon/EVA
- PVC bridge

LENS MATERIAL AVAILABLE

- CR39
- Polycarbonate

+ SIDE SHIELDS

+ NON-SLIP BRIDGE

+ NON-SLIP TEMPLES

bolle
SAFETY

HUSTLER RX

DESIGN AT THE SERVICE OF PROTECTION

MODEL	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
HUSTLER RX	HUSTN	68/17	EN166 F C€	120 mm

LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

FRAME MARKING

EN 166 : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

€ European standard ☞ Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power: +7/-6

Maximum cylinder compared with sphere : 5

CORRECTED BASE:

Corrected base : 8

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

Minimum mono PD : 31mm

PACKAGING AND EAN13 CODE

	HUSTN
Per piece	3660740008413

CHARACTERISTICS

LENS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Free form - Degressive
FRAME	Nylon/EVA
BRIDGE	PVC



17/07/2017

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY