

# BOSS

## PROTECTS IN ANY SITUATION

Also available in our prescription range, BOSS provides extensive protection in most circumstances. The straight temples feature rubber tips for enhanced grip and extra stability and comfort.



BOSSPSI

AVAILABLE IN  
**RX**



30 g

SUPPLIED WITH

Adjustable cord  
CORDC






- + UPPER PROTECTION**
- + NON-SLIP BRIDGE**
- + LOWER PROTECTION**

**bolle**  
SAFETY

# BOSS

## PROTECTS IN ANY SITUATION

| MODEL       | VERSIONS  | REFERENCES | LENS MARKING   | FRAME MARKING   | COATINGS                      |
|-------------|---|------------|--|---|-------------------------------|
| <b>BOSS</b> |  Clear | BOSSPSI    | 2-1,2  1 FT KN €€ |  EN166 FT €€ | Anti-scratch (K)/Anti-fog (N) |

### LENS MARKING


#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:


- K.** Resistance to surface damage by fine particles (optional)
- N.** Resistance to fogging (optional)
- €€ European standard  Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

| PACKAGING AND EAN13 CODE             |                |
|--------------------------------------|----------------|
|                                      | <b>BOSSPSI</b> |
| Individual plastic bag               | 3660740000714  |
| 10 safety spectacles per inner box   | 3660740100711  |
| 240 safety spectacles per outer pack | 3660740200718  |

| CHARACTERISTICS |                              |
|-----------------|------------------------------|
| LENSES          | <b>PC - 2,2 mm - Curve 8</b> |
| FRAME           | <b>PC</b>                    |
| TEMPLES         | <b>PC + TPR</b>              |
| STRAP           | <b>Non applicable</b>        |
| FOAM            | <b>Non applicable</b>        |
| SPARE LENSES    | <b>No</b>                    |



01/10/2013

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY