

# TRYON OTG

## ULTRA-COVERING

TRYON is available in Premium OTG version. Beneficiating from PLATINUM® coating, maximal covering, extendable temples allowing a precise adjustment to every wearer. TRYON OTG is compatible with most of prescription spectacles.

 PLATINUM®



41g



TRYOTGPSI











TRYOTGPSF

- + **SOFT UPPER PROTECTION (TPR)**
- +  **PLATINUM® COATING ( +P )**
- + **CO-INJECTED PC/TPR ADJUSTABLE AND EXTENDABLE TEMPLES**
- + **FLEX 160° TEMPLES**

**bolle**  
SAFETY

# TRYON OTG

## ULTRA-COVERING

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
TRYON OTG	 Clear	TRYOTGPSI	2C-1,2  1 FT KN €€	 EN166 FT €€	Anti-scratch/Anti-fog 
	 Smoke	TRYOTGPSF	5-3,1  1 FT KN €€	 EN166 FT €€	Anti-scratch/Anti-fog 

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:


F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging


€€ European standard  Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### TECHNOLOGIES



The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE		
	TRYOTGPSI	TRYOTGPSF
Individual plastic bag	3660740008307	3660740008420
10 spectacles per inner box	3660740108304	3660740108427
180 spectacles per outer pack	3660740208301	3660740208424

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 4
FRAME	-
TEMPLES	PC + TPR
UPPER PROTECTION	TPR
SPARE LENSES	No



Non-contractual pictures

18/04/2017

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle-safety.com**

**bolle**  
SAFETY