

# B808

## PROTECTIVE AND LIGHTWEIGHT

The best seller in the prescription line, the B808 is now available in the spectacle range. Lightweight, stylish and wrap-around, the B808 is a guaranteed success!

 PLATINUM



B808BLPSI







28 g

- + UPPER AND SIDE PROTECTION**
- + WRAP-AROUND FIT**
- +  PLATINUM COATING ( +P )**

**bolle**  
SAFETY

# B808

## PROTECTIVE AND LIGHTWEIGHT

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>B808</b>	 Clear	B808BLPSI	2C-1,2  1 F KN C€	 EN166 F C€	Anti-scratch/Anti-fog (  )

### LENS MARKING

#### Optical class symbols:

1. Continuous work


#### Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

#### Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

C€ European standard  Manufacturer name

### TECHNOLOGY

#### PLATINUM

The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

### FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

C€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly with a mild soap detergent or optical solution.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** Store between 5 and 40 °, humidity <90%.

### PACKAGING AND EAN13 CODE

	B808BLPSI
Individual plastic bag	3660740007218
10 safety spectacles per inner box	3660740107215
240 safety spectacles per outer pack	3660740207212

### CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 4
FRAME	PC
TEMPLES	PC
STRAP	No
FOAM	No
SPARE LENSES	No



Non-contractual pictures

21/05/2014

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY